



Dimensions

| Positions | C | D | E | F | G |
|-----------|-------|-------|-------|-------|-------|
| 14 | 25,10 | 17,70 | 12,96 | 44,00 | 36,00 |
| 24 | 35,80 | 28,74 | 23,76 | 54,76 | 46,80 |
| 36 | 48,90 | 41,60 | 36,72 | 67,82 | 59,70 |
| 50 | 64,06 | 56,70 | 51,84 | 82,92 | 74,90 |

- NOTES:**
- MATERIAL**
1. Insulator Material: Glass-Filled Thermoplastic PBT, UL94V-0 rated
 2. Contact : Brass; Gold flash selective Gold plating
 3. Shells : Steel , 100µ" Tin over 50µ" min Nickel
- ELECTRICAL**
1. Current Rating : 5AMP
 2. Dielectric Withstanding Voltage : 1000VAC/rms 60Hz for 1 minute
 3. Insulation Resistance: 1000MΩ at 500V DC
 4. Contact Resistance: 20 milliohms Max at 3 AMP DC.
 5. Voltage Rating : 250 VAC/rms 60 Hz

RoHS compliant

| Scale | 1:1 | | | | | | |
|-----------|-------|---|--------|------------|---------|--|--|
| TOLERANCE | | | | | | | |
| X. | ±0,38 | | | | | | |
| X.X | ±0,25 | | | | | | |
| X.XX | ±0,13 | ③ | Update | 25.04.2013 | Winnie | | |
| X.° | ±3° | ② | Redraw | 23.03.2009 | Dean | | |
| X.X° | ±1° | ① | Drawn | 22.06.2007 | Hellwig | | |
| X.XX° | ±X° | | | | | | |
| X.XXX° | ±X° | | Id. | | | | |

| Date | Name | Customer-No. | Drawing-No. | Replace | Sheet |
|------------|---------|--------------|-----------------|--------------|-------|
| 22.06.2007 | Hellwig | | ASSMANN WSW-No. | ASS 0361A CO | rev03 |
| 25.04.2013 | Winnie | | A-57/XX FR/KL-A | | |

ASSMANN
W S W / components

| | | | | | | | |
|---|---|---|---|---|---|---|---|
| 1 | 2 | 3 | 4 | 5 | 6 | 7 | A |
| 1 | 2 | 3 | 4 | 5 | 6 | 7 | H |
| 1 | 2 | 3 | 4 | 5 | 6 | 7 | G |
| 1 | 2 | 3 | 4 | 5 | 6 | 7 | F |
| 1 | 2 | 3 | 4 | 5 | 6 | 7 | E |
| 1 | 2 | 3 | 4 | 5 | 6 | 7 | D |
| 1 | 2 | 3 | 4 | 5 | 6 | 7 | C |
| 1 | 2 | 3 | 4 | 5 | 6 | 7 | B |
| 1 | 2 | 3 | 4 | 5 | 6 | 7 | A |