



NOTES:

MATERIAL

- 1.Insulator Material:PBT+30%G.F.(UL94V-0),Black
- 2.Contact Material : Brass
- 3.Contact Plating : Gold Flash over Ni

ELECTRICAL

- 1.Current Rating : 3.0AMP
- 2.Withstand Voltage : 1000V AC/minute
- 3.Contact Resistance : 20mΩ max
- 4.Insulation Resistance: 1000MΩ min

ENVIRONMENTAL

- 1.Operation Temperature: -40°C to +105°C
- 2.Packing: Tray
- 3.No side slot "A" and "B" from 6 to 16 pin
No side slot "A" from 18 to 58 pin

Ordering Information

AWH xxG-02x2-LC

No. of Contacts:
06,08,10,12,14,16,18,20
24,26,30,34,40,50,60,64

Latch Type:
0 -without latch
2 -with short latches
3 -with long latches

RoHS compliant
Unit: mm



Scale	Free						Date	Name	Customer-No.
TOLERANCE		⑤	Add UL file no.	12.12.2013	Amy	Drawn	21.02.2002	Hellwig	ASSMANN WSW-No. AWH xxG-02x2-LC
X.X	±0.40	④	Correct drawing of short latch	05.05.2010	Dean	Approved	12.12.2013	Amy	
X.XX	±0.25	③	Modify dimensions	03.11.2009	Dean				
X.XXX	±0.15	③	Modify dimensions	03.11.2009	Dean				Drawing-No.
Angle	±3°	②	Redraw	26.03.2009	Dean				ASS 1247A CO rev05
		①	Drawn	21.02.2002	Hellwig				Sheet
		Id.	Modification	Date	Name				

