



No.	DESCRIPTION	QTY	UNIT
6	NUTS:4.75*2.0MM<4#-40UNC>	4	PCS
5	PVC-BLACK10/30P <UL94V-0>	18.0	G
4	PVC-IN	11.0	G
3	FOIL-CU-20MM	30*2	MM
2	USB-A/S-9P(BLUE)<PIN G/F>	2	SET
1	UL20276-(28#*1P+D+A+M)*2C+30#*1P+24#*2C+A+B,BLACK10,Ø5.5<USB 3.0>	2.48	M

NOTE:
 1. 100% short, open, miss wire test;
 2. 100% characteristic impedance test.

Order code:
 A-USB30AF-30AF-50 L= 500mm
 A-USB30AF-30AF-100 L= 1000mm
 A-USB30AF-30AF-2500 L= 2500mm

RoHS compliant
 Unit: mm

Scale	Free	Date	Name	Customer-No.	
TOLERANCE		Drawn	14.02.2017	Amy	
		Approved	14.02.2017	Amy	
DIM	TOL				
Angle	TOL				
		① Drawn	14.02.2017	Amy	
		Id.	Modification	Date	Name

ASSMANN WSW-No. A-USB30AF-30AF-xxx	
Drawing-No. ASS_7847A_CA	rev00
Replace	Sheet