



NOTES:
Electrical test:
 1. 100% short , open , miswire test
 2. Conduct resistance : 2 Ohm max
 3. Insulator resistance : 5 Mohm min
 4. Hi-Pot : DC 300V

WIRING DIAGRAM:

P1	1	2	3	4	5	6	7	~	35	36	37	38	39	40
P2	1	2	3	4	5	6	7	~	35	36	37	38	39	40
CABLE	RED	GRAY												

No.	Name	QTY	Specification
⑥	RUBBER	1/10	Transparent rubber
⑤	PE BAG	1/10	CLEAR SIZE:260*180*0.05mm PRINT BLACK"MADE IN CHINA""10PC"
④	CONN	2	IDC 40P PH2.54MM SR COLOR BLACK
③	CONN	3	IDC 40P PH2.54MM MIDDLE COVER COLOR BLACK
②	CONN	3	IDC 40P PH2.54MM PIN BRASS G/F COLOR BLACK
①	Cable	1	UL2651 28AWG 40P PH1.27 COLOR GRAY WITH RED LINE L+530+10/-0mm

RoHS compliant
 Unit: mm

Scale	Free	Customer-No.	ASSMANN WSW-No.
TOLERANCE		Drawn	AK5430-.5
		Approved	
DIM	TOL	Date	Name
		14.12.2017	Winnie
Angle	TOL		
		Drawing-No. ASS 8157 CA Replace rev00 Sheet	

1	2	3	4	5	6	7
---	---	---	---	---	---	---